

EPT20-15ET

Electric Pallet Truck 1.5t

- 1st Innovative Design Ever
- Compact Size & Light Weight, Convenient for Operation
- Energy-saving & environment-friendly design maximizes running time
- Incredible Market Share Globally
- Can replace drive wheel only by releasing six nuts



CE

■ FEATURE

■ Innovation:

1st Innovative Design Ever won the REDDOT award.

■ Light Weight, Great Capacity, Great Pa -ssingability:

Light weight & compact size create excellent manuverability & passingability. 1500KG capacity handles most applications.



Special anti-vibration technology extends maintenance-free battery life.

Operation:

Ergonomically-designed tiller head helps increase efficiency; Internal Charger for Easy Charging.







■ Cables:

Robot cables with excellent twist resistance offers longer life span.

Button & Durable Driving Unit ensure safety under any situation.



Handy Emergency Disconnect





option

■ Charger:

Charger with temperature indicator protects battery.

Serviceability:

Assembly Components, Easy for Diagnosis and Replacing.


Can replace drive wheel only by releasing six nuts




Electric Pallet Truck 1.5t EPT20-15ET

Distinguishing mark	1.1 1.2 1.3	Manufacturer Model designation			EP
guishing mark		woder designation			EDTO0 4FET
guishing m	1.3	Daire			EPT20-15ET
guishir		Drive			Electric Pedestrian
n <u>6</u>	1.4	Operator type	0	1.0	
_ ⊆	1.5	Load capacity	Q	kg	1500
Disti	1.6	Load center distance	С	mm	600
	1.8	Load distance, centre of drive axle to fork	X	mm	883/946
	1.9	Wheelbase	у	mm	1228/1268
jht Jht	2.1	Service weight		kg	210
Service	2.2	Axle loading, laden front/rear		kg	574/1131
	2.3	Axle loading, unladen front/rear		kg	165/40
	3.1	Tyre type			Polyurethane
w	3.2.1	Tyre size, front		mm	Ф210х70
a ssi	3.3.1	Tyre size, rear		mm	Ф80х61 (Ф74х88)
Tyre s/chassis	3.4	Additional wheels (castor wheels)		mm	_
Tyre	3.5	Wheels, number front/rear (x=drive wheels)		mm	1x, — /4
	3.6.1	Tread width, front	b10	mm	_
	3.7.1	Tread width, rear	b11	mm	410 (535)
	4.4	Lift height	h3	mm	115
	4.9	Height of tiller handle in drive position min./max.	h14	mm	750/1170
	4.15	Lowered height	h13	mm	85 (75)
	4.19	Overall length	l1	mm	1632
<u>s</u>	4.20	Length to face of forks	12	mm	482
sion	4.21	Overall width	b1/b2	mm	560 (685)
Dimensions	4.22	Fork dimensions	s/e/I	mm	50/150/1150
ā	4.25	Distance between fork-arms	b5	mm	560 (685)
	4.32	Ground clearance, center of wheelbase	m2	mm	35(25)
	4.34.1	Aisle width for pallets 1000×1200 crossways	Ast	mm	2290
	4.34.2	Aisle width for pallets 800×1200 crossways	Ast	mm	2160
	4.35	Turning radius	Wa	mm	1485
	5.1	Travel speed, laden/unladen		km/ h	4/4.5
e da	5.2	Lifting speed, laden/unladen		m/s	0.022/0.025
ance	5.3	Lowering speed, laden/unladen		m/s	0.034/0.023
rformance data	5.8	Max. gradeability, laden/unladen		%	5/16
Perl	5.10	Service brake			Electromagnetic
	6.1	Drive motor rating S2 60 min		kW	0.65
Electric-engine	6.2	Lift motor rating at S3 15%		kW	0.84
tric.	6.4	Battery voltage/nominal capacity		V/Ah	2x12V/85Ah
- Ile Ci	6.5	Battery weight		kg	25.5x2
	8.1	Type of drive control			DC
Addition data	10.5	Steering design			Mechanical
Adc	10.7	Sound pressure level at the driver's ear		dB(A)	74

If there are improvements of technical parameters or configurations, no further notice will be given. The diagram shown may contain non-standard configurations.





Option

No.	Optional items	EPT20-15ET		
1.1	Fork length	●1150○1000○1220		
1.2	Fork width	●560°685		
1.3	Fork lowered height	●85°75°60°40		
1.4	Fork carriage width	∘560∘685		
1.5	Fork carriage height	∘1220mm (48in) ∘1520mm (60in)		
2.1	Load wheel type	• Double∘ Single		
2.2	Load wheel material	●PU		
2.3	Drive wheel material	●PU∘Trace PU		
2.7	Battery capacity	●85Ah		
2.8	Charger	●24V-15A inside		
2.9	Battery indicator	●Without time○With time		
3.3	Castor wheels	∙No∘Yes		
3.16	Vertical handler working	∙No∘Yes		
4.4	Weighting system with fork	 Yes and not customized 		
Note: ∙Sta	andard o Optional - Inconformity			









- **L** +31 (0)172 42 42 20
- info@tramag.nl
- ⊕ www.tramag.nl
- Harsweg 21 2461 EZ Ter Aar