



## ECONOMICAL MANUAL STACKER

Ideal and economic choice for manual transport and lifting, with its different mast options (1600, 3000 mm) and diverse lifting capacity (500kg, 1000kg) enables to deal with a large number of applications in the warehouse or any other facilities. For example, with the lift capacity of 1000 kg and lifting height of 1600mm, therefore the truck is an ideal and economic choice suitable for first level stacking.

- The minimized turning radius and compact size of the truck allows it to be used in the most confined space and narrow aisle such as in stores, small warehouses and factories.



Easy and comfortable handling through ergonomically handles, effortless pulling during transport with long tiller



We can offer additional protection for the operator through foot protection on the steering rollers. Safe parking in any situation with mechanical parking brake.



### Model TEFS series

ITEM/TYPE		TEFS1016	TEFS1030
Capacity Q	Kg	1000	1000
Load center c	mm	600	600
Max.Fork Height	mm	1600	3000
Lowered Fork Height	mm	85	85
Fork Adjust Width	mm	550	550
Fork Width	mm	160	160
Fork Length	mm	1150	1150
Overall length	mm	1660	1668
Overall height	mm	2010	2060
Overall width	mm	740	740
Ground Clearance	mm	25	25
Front Wheel	mm	φ 74x55	φ 74x70
Rear Wheel	mm	φ 180x50	φ 180x50
Net weight	Kg	172	310

